

DESCRIPTION

Ultra-thin design, light thickness only 1.2", spring loaded retention arms allow for easy installation into ceilings with no need for a recessed housing.

Rated IC, by design of lamp tilt Angle, highlight speci7c areas. Fixture color temperature range from 2700-5000K. Meet your different needs in the hallway, living room, kitchen, bedroom and even walk-in closet.

Available sizes: 4 ", 6"



FEATURES

- Fully enclosed aluminum housing
- · Easy to install, no housing required
- Edge lit technology allows for extremely thin fixture depth

INSTALLATION

No existing recessed housing or junction box required.

Suitable for most new constructions.

Install J-Box in ceiling beam, and insert light right into drywall opening.

DIMMING

Compatible with most triac dimmers to give user a smooth 100%-5% dimming to choose the desired brightness.

ELECTRICAL

This fixture is built with the highest quality 120V drivers, ensuring energy efficiency.

SPECIFICATION

Model: 4EJCT09SR05G

Size: 4inchWattage: 9W

Lumens: 630lm/673lm/693lm/707lm/668lm

Voltage: 120V

Power Frequency: 60Hz

• Power Factor: >0.9

5CCT: 2700K/3000K/3500K/4000K/5000K

CRI: 90

Beam Angle: 120°Material: AL+PS

Lifespan: ≥50,000hours

Operating Temp: (-4°F~ 122°F) -20~40°C

Dimmable: Triac Dimming

Rating: Suitable for Wet Locations

Warranty: 5 year limited

ENERGY SAVINGS

80% more energy savings than halogen lamps.

LISTING

ETL Listed.









Product View

Beam Angle 120°



Can be tilt adjusted ±10° from the horizontal position.




Easily flip the switch for desired CCT



DIMENSION

Size	А	В	С	D	E
4inch	Φ5.2"(132mm)	1.2"(30.7mm)	4.73"(120.1mm)	2.77"(70.4mm)	1.34"(34.1mm)
6inch	Ф7.36"(187mm)	1.2"(30.7mm)	4.73"(120.1mm)	2.77"(70.4mm)	1.34"(34.1mm)



RECOMMENDED DIMMER

	LUTF	LEVITON			
TG-600PR-WH S-600PR-WH CTCL-153PDH-WH	TGCL-153PH-LA SLV-600P-AL DV-600PR-WH	SCL-153PH-WH GT-600P DVCL-153P	RNL06 MSCL-OP153M IPL06	6672 6674 DSL06	PD-6WCL MACL-153M//MA-R

HOLE SIZE & ACCESSORIES

