

DESCRIPTION

Ultra slim design, lamp thickness only 0.49". Features color tunable technology lets the user choose between 2700K, 3000K, 3500K, 4000K, or 5000K. IC rated for direct contact with insulation.

Wet-location rated, ideal for bathrooms, laundry, porches and garage work rooms.

Available size: 4", 6"



FEATURES

- Edge-lit technology, with no glare or dark spots
- Continuous dimming from 100% to 10% with many Triac Dimmers
- Instant on
- No flicker

INSTALLATION

No existing recessed housing or junction box required.

Suitable for most new constructions.

Install J-Box in ceiling beam, and insert light right into drywall opening.

DIMMING

Compatible with most triac dimmers to give user a smooth 100%-10% dimming to choose the desired brightness.

ELECTRICAL

This fixture is built with the highest quality 120V drivers, ensuring energy efficiency.

LISTING

ETL Listed.

SPECIFICATION

Model: 4EJCT09SS05

Size: 4inchWattage: 9W

Lumens:525Lm/561Lm/587Lm/600Lm/588

Lm

Voltage: 120V

Power Frequency: 60Hz

Power Factor: >0.9

5CCT: 2700K/3000K/3500K/4000K/5000K

CRI: 90

Beam Angle: 120°Material: AL+PS

Lifespan: ≥50,000hours

Operating Temp: (-4°F~ 122°F) -20~40°C

Dimmable: Triac dimming

Rating: Suitable for Wet Locations

Warranty: 5 year limited

ENERGY SAVINGS

80% more energy savings than halogen lamps.











Product View

4inch&6inch: Easily flip the switch for desired CCT









SIZE & DIMENSION & HOLE SIZE





SIZE	A	В	С	D	Е	F
4inch	4.96"(126mm)	4.96"(126mm)	0.49"(12.45mm)	4.73"(120.1mm)	2.77"(70.4mm)	1.34"(34.1mm)
6inch	6.93"(176mm)	6.93"(176mm)	0.49 (12.4311111)	4.73 (120.111111)	2.77 (70.411111)	1.54 (54.111111)

SIZE	HOLE SIZE
4inch	4 21/64"(110mm)
6inch	6 19/64"(160mm)



RECOMMENDED DIMMER

	LUTF	RON		L	.EVITON
TG-600PR-WH S-600PR-WH CTCL-153PDH-WH	TGCL-153PH-LA SLV-600P-AL DV-600PR-WH	SCL-153PH-WH GT-600P DVCL-153P	RNL06 MSCL-OP153M IPL06	6672 6674 DSL06	PD-6WCL MACL-153M//MA-R

ACCESSORIES				
PART	DESCRIPTION	QUANTITY		
Α	J-Box driver	1		
В	Connector	3		
С	Hole cutout card	1		





