

DESCRIPTION

Ultra slim design, lamp thickness only 0.49". Features color tunable technology lets the user choose between 2700K, 3000K, 3500K, 4000K, or 5000K. 3 levels of adjustable wattage. IC rated for direct contact with insulation.

Wet-location rated, ideal for bathrooms, laundry, porches and garage work rooms.

Available size: 4", 6"



FEATURES

- Edge-lit technology, with no glare or dark spots
- Continuous dimming from 100% to 10% with many Triac Dimmers
- Instant on
- No flicker

INSTALLATION

No existing recessed housing or junction box required.

Suitable for most new constructions.

Install J-Box in ceiling beam, and insert light right into drywall opening.

DIMMING

Compatible with most triac dimmers to give user a smooth 100%-10% dimming to choose the desired brightness.

ELECTRICAL

This fixture is built with the highest quality 120V drivers, ensuring energy efficiency.

SPECIFICATION

- Model: 4EJCTSS05
- Size: 4inch
- Wattage: 8W-10W-12W
- Lumens:492Lm-610Lm-741Lm / 508Lm-621Lm-754Lm / 514Lm-636Lm-767Lm / 520Lm-650Lm-780Lm / 506Lm-631Lm-760Lm
- Voltage: 120V
- Power Frequency: 60Hz
- Power Factor: >0.9
- 5CCT: 2700K/3000K/3500K/4000K/5000K
- CRI: 90
- Beam Angle: 120°
- Material: AL+PS
- Lifespan: ≥50,000hours
- Operating Temp: (-4°F~ 122°F) -20~40°C
- Dimmable: Triac dimming
- Rating: Suitable for Wet Locations
- Warranty: 5 year limited

ENERGY SAVINGS

80% more energy savings than halogen lamps.

LISTING

ETL Listed.











Product View



Selectable CCT & Selectable Wattage





DIMENSION






SIZE	А	В	С	D	E	F
4inch	4.96"(126mm)	4.96"(126mm)	0.49"(12.45mm)	4.73"(120.1mm)	2.77"(70.4mm)	1.34"(34.1mm)
6inch	6.93"(176mm)	6.93"(176mm)	0.49"(12.45mm)	4.73"(120.1mm)	2.77"(70.4mm)	1.34"(34.1mm)

RECOMMENDED DIMMER

	LUTF	LEVITON			
TG-600PR-WH S-600PR-WH CTCL-153PDH-WH	TGCL-153PH-LA SLV-600P-AL DV-600PR-WH	SCL-153PH-WH GT-600P DVCL-153P	RNL06 MSCL-OP153M IPL06	6672 6674 DSL06	PD-6WCL MACL-153M//MA-R

HOLE SIZE ACCESSORIES



SIZE	HOLE SIZE
4inch	4 21/64"(110mm)
6inch	6 19/64"(160mm)







Connector