

## DESCRIPTION

PC driver housing and Aluminum reflector with architectural white finish. Easy clip-in to existing can housing. Features color tunable technology lets the user choose between 2700K, 3000K, 3500K, 4000K, or 5000K. 3 levels of adjustable wattage. Damp-location rated, ideal for residential housings, hotels, corridors, home decoration, shopping malls, schools.

Available size: 4", 6"



## FEATURES

- Emits evenly, without halo or shadows.
- Continuous dimming from 100% to 5% with many Triac Dimmers
- Baffle/Smooth finish option
- Color removable trim available (sold separately): Brushed nickel, Black, Bronze. Baffle/Smooth trim option.

## INSTALLATION

Fit in 4 , 5/6 inch compatible housing cans directly, no additional accessories are required.

## DIMMING

Compatible with most triac dimmers to give user a smooth 100%-5% dimming to choose the desired brightness.

## ELECTRICAL

This fixture is built with the highest quality 120V drivers, ensuring energy efficiency.

## SPECIFICATION

- Model: 4HVCTLR05WH10W
- Size: 4inch
- Wattage: 10W
- Lumens: 679lm/776lm/760lm/712lm/658lm
- Voltage: 120V
- Power Frequency: 60Hz
- Power Factor: >0.9
- 5CCT: 2700K/3000K/3500K/4000K/5000K
- CRI: 90
- Beam Angle: 100°
- Material: PS+AL
- Lifespan: ≥50,000hours
- Operating Temp: (-4°F~ 113°F) -20~45°C
- Dimmable: Triac Dimming
- Rating: Suitable for Damp Locations
- Warranty: 5 year limited

## ENERGY SAVINGS


80% more energy savings than halogen lamps.

## LISTING



ETL Listed. Energy Star. Title24.



**Product View**



**DIMENSION**



**RECOMMENDED DIMMER**

LUTRON				LEVITON	
TG-600PR-WH	TGCL-153PH-LA	SCL-153PH-WH	RNL06	6672	PD-6WCL MACL-153M//MA-R
S-600PR-WH	SLV-600P-AL	GT-600P	MSCL-OP153M	6674	
CTCL-153PDH-WH	DV-600PR-WH	DVCL-153P	IPL06	DSL06	

**ACCESSORIES**



E26 Adapter

**REMOVABLE TRIM(SOLD SEPARATELY)**



Brushed nickel



Black



Bronze