

DESCRIPTION

This flush mount panel light is designed for comfortable illumination in office, home, hotels, corridors, shopping malls, schools.

Features color tunable technology lets the user choose between 2700K, 3000K, 3500K, 4000K, or 5000K.

Available size: 5", 7", 9"



FEATURES

- Emits evenly, without halo and shadow
- Fit 4" J-Box and 5"/6" Housing
- 2 installation ways supporting: Suface mount and Retrofit
- Color removable trim available (sold separately): Brushed Nickel, Black, Bronze

STYLISH AND SLIM DESIGN

This ultra bright LED Flush Mount is only 0.5 inch thickness.

The smooth surface is suitable for a variety of decorative styles.

DIMMING

Compatible with most triac dimmers to give user a smooth 100%-10% dimming to choose the desired brightness.

ELECTRICAL

This fixture is built with the highest quality 120V drivers, ensuring energy efficiency.

SPECIFICATION

- Model: 7FMCT15SR05WH
- Size: 7inchWattage: 15W
- vvallage. 15vvLumens:
 - 980lm/1044lm/1090lm/1127lm/1072lm
- Voltage: 120V
- Power Frequency: 60Hz
- Power Factor: >0.9
- 5CCT: 2700K/3000K/3500K/4000K/5000K
- CRI: 90
- Beam Angle: 120°
- Material: AL+ Plastic + PS
- Lifespan: ≥50,000hours
- Operating Temp: (-4°F~ 113°F) -20~45°C
- Dimmable: Triac Dimming
- Rating: Suitable for Damp Locations
- Warranty: 5 year limited

ENERGY SAVINGS

80% more energy savings than halogen lamps.

LISTING

ETL Listed. Energy Star. Title 24.













Product View

7inch & 9inchEasily flip the switch for desired CCT




Products View




Recommended Dimmer

LUTRON		LEVITON
TG-600PR-WH S-600PR-WH CTCL-153PDH-WH TGCL-153PH-LA SLV-600P-AL DV-600PR-WH		6672 6674 DSL06 PD-6WCL MACL-153M//MA-R

SIZE & DIMENSION





SIZE	А	В	С
7inch	,	0.5"(12.75mm)	1"(25.5mm)
9inch	Ф8.86"(225mm)	0.5"(12.75mm)	1"(25.5mm)

REMOVABLE TRIM(SOLD SEPARATELY)







ACCESSORIES

SURFACE MOUNT ACCESSORIES				
PART	DESCRIPTION	QUANTITY		
a d e	Mounting Bracket Wire Nuts Screws 1	1 3 2		

RETROFIT INSTALLATION ACCESSORIES				
PART	DESCRIPTION	QUANTITY		
а	Mounting Bracket	1		
b C	Springs E26 Adapter	2		
d	Wire Nuts	3		
f	Screws 2	2		



