

Application:

VP104R 27-watt Indoor/Outdoor Integrated LED Vapor Tight Light Ceiling and Wall Light is a high performance, low-maintenance, dependable and reliable area and security lighting solution. Suitable for wall or ceiling mounting and equals, approximately of a 300-Watt standard incandescent light bulb output. This area light is ideal for residential and commercial applications such as entrances, patios, walkways, apartment complexes, parking garages, outlet exteriors, storage areas, common areas, workshops and hotels or wherever vapor tight applications apply.



- Durable die-cast aluminum housing with heavy-duty glass globe
- Die-cast aluminum quard provides protection against vandalism
- 1/2" threaded opening allows for conduit entry
- Inbuilt color temperature & wattage adjustable switch
- Designed for easy installation and maintenance
- Frosted glass globe for even distribution (optional)
- Frosted PC lens also available (optional)
- Junction box included


Technical Specification	
Model Number	VP104R
Input Voltage	120-277V
Power Factor	>0.9
THD	<20%
CRI	>70
Ambient Operating Temperature	-40~30°C
Color Temperature	3000K/4000K/5000K (Selectable)
Wattage: Long Frosted PC lens	27W(3000lm) (50%, 75%, 100%)
Wattage: Long Frosted Glass lens	26W(2584lm) (50%, 75%, 100%)
Efficacy	Up to 114lm/w
Surge Protection	4KV included








Dimensions



VP104R-C



VP104R-W